







# Newsletter November 2010

We have extended our range of Clack valves to include the following models:

	<b>WS1</b>	<b>WS1 CI</b>	<b>WS1.5 CI</b>	<b>WS2 CI</b>	<b>WS2 H</b>	<b>WS3</b>
						
Regeneration Options	Timeclock or External contact	Timelcock, metered or external contact	Timelcock, metered or external contact	Timelcock, metered or external contact	Timelcock, metered or external contact	Timelcock, metered or external contact
Flow rates	Flow 6m3/hr B/W 6m3/hr	Flow 6m3/hr B/W 6m3/hr	Flow 13m3/hr B/W 11m3/hr	Flow 26m3/hr B/W 18m3/hr	Flow 28m3/hr B/W 28m3/hr	Flow 56m3/hr B/W 50m3/hr
Special features	Most economical version for filters	Options of no hard water bypass and duplexing adapter.	Options of no hard water bypass and duplexing adapter.	Options of no hard water bypass and duplexing adapter.	Capable of multiple installations (upto 4)	Capable of multiple installations (upto 4)
Filter Softener t/c Softener metered Filter metered	VCWS1-3B+TR VCWS1-3B-T/C	VCWS1-FILTER+TR VCWS1-T/C+TR VCWS-MET+TR	VCWS15CIBTZ-05 VCWS15CIDTG-05 VCWS15CIDMG-05	VCWS2CI-FILT VCWS2CI-T/CLOCK VCWS2CI-MET	VCXS2H-MET VCXS2H-FILT-MET	VCWS3-FILTER VCWS3-T/C VCWS3-MET

All of our filters and softeners can be specified with Clack valves, please see our price list or call us for details

### Deliveries

Please check all deliveries before signing.

Signing "unchecked" is classed as an unqualified statement by carriers & their insurance companies and therefore not recognised by them.

Please give us a call if you have any questions regarding deliveries.

### Latest Projects

The photograph below shows a custom designed RO built with a CIP facility, dual conductivity meters and microprocessor control.



### Clack Duplex

With the use of a motorised alternating valve, the Clack's can be used as a duplex system.



# Euraqua UK - New Products



The Cintropur range of filters can be used for any domestic or industrial application where sediment filtration is required. Flow rates range from 3.5m<sup>3</sup>/hr to 30m<sup>3</sup>/hr and the standard filtration sleeves have a pore size of 25 microns though 5, 10 & 50 micron sleeves are also available. Connection sizes range from 3/4" to 3" and we supply pressure gauges on units with 2" ports upwards. Brass socket connections are also available for filters with 2" connections or larger.



## Advantages

High flow rates

Low pressure drops

Centrifugal pre-filtration with a cyclonal effect

Transparent bowl allowing visual checks

## New Lower Prices!

### Example: Cintropur NW50

Flow rate 20m<sup>3</sup>/hr

Includes 2 x pressure gauges

**Price £194**

### Example: Cintropur NW75

Flow rate 30m<sup>3</sup>/hr

Includes 2 x pressure gauges

**Price £207**

### Example: Cintropur NW18

Flow rate 3.5m<sup>3</sup>/hr

**Price £40**



Carbon option



Also available:  
Filter bags, wall mounting brackets,  
pressure gauges, connectors.

Call us for more details, data sheets and prices

**The Right Product**

.....At The Right Price

.....At The Right Time

# Euraqua UK

22 Cam Centre

Wilbury Way

Hitchin

Herts SG4 0TW

Tel: 01462 421199

Fax: 01462 420779

email: [sales@eur aqua.co.uk](mailto:sales@eur aqua.co.uk)

[orders@eur aqua.co.uk](mailto:orders@eur aqua.co.uk)

Web site: [www.eur aqua.co.uk](http://www.eur aqua.co.uk)